

Application No. 10/027,814  
Amendment dated January 25, 2005  
Reply to Final Office Action of November 26, 2004

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (CANCELLED)
2. (CURRENTLY AMENDED) The oil pan of claim 16 ~~[[1]]~~, wherein the reinforcement channels are substantially U shaped.
3. (CURRENTLY AMENDED) The oil pan of claim 16 ~~[[1]]~~, wherein the reinforcement channels are V-shaped.
4. (CURRENTLY AMENDED) The oil pan of claim 16 ~~[[1]]~~, wherein the second end of the oil pan has an end surface which is substantially planar.
5. (ORIGINAL) The oil pan of claim 4, wherein said end surface has no tool access pockets therein.
6. (CURRENTLY AMENDED) The oil pan of claim 16 ~~[[1]]~~, wherein adjacent the second end and intermediate the width of the second end, the oil pan has a region of reduced height, and wherein the region of reduced height having a planar portion into which the at least one reinforcing channel does not extend.

Application No. 10/027,814  
Amendment dated January 25, 2005  
Reply to Final Office Action of November 26, 2004

7. (ORIGINAL) The oil pan of claim 6, wherein the planar portion is adapted to releasably receive thereon a horizontal portion of a substantially L-shaped cover plate.

8. (ORIGINAL) The oil pan of claim 7, wherein the cover plate has a substantially upright portion such that when the cover plate is mounted on the planar portion, the substantially upright portion is substantially coplanar with the end surface.

9. (ORIGINAL) The oil pan of claim 8, wherein the substantially upright portion has a securing flange at an end thereof remote from the horizontal portion.

10. (CURRENTLY AMENDED) The oil pan of claim 16 ~~[[1]]~~, wherein the channels tapering downwardly from the first end and the second end are created by curving the channels.

11. (ORIGINAL) The oil pan of claim 10, wherein the channels have a radius of curvature that is 2000mm.

12. (CANCELLED)

13. (CURRENTLY AMENDED) The oil pan of claim 16 ~~[[12]]~~, wherein the oil pan has a region of reduced height and the main body has a second end wall which tapers into the region of reduced height.

14. (CURRENTLY AMENDED) The oil pan of claim 16 ~~[[1]]~~, wherein there are no channels in the accumulation area.

Application No. 10/027,814  
Amendment dated January 25, 2005  
Reply to Final Office Action of November 26, 2004

15. (CURRENTLY AMENDED) The oil pan of claim 16 ~~[[12]]~~, wherein the channels extend up the first end wall but at a reducing height up the first end wall.

16. (CURRENTLY AMENDED) An oil pan for an engine comprising:  
a plurality of substantially parallel, spaced-apart reinforcement channels extending from adjacent a first end of the oil pan to adjacent a second end of the oil pan, each channel having a base and two sides and an open top, the channels tapering downwardly from the first end and the second end towards an accumulation area of the oil pan, wherein the oil pan has a region of reduced height and a main body, the main body having two side walls, a first end wall, and a base, and wherein the accumulation area is integral with the base and the channel walls along the base are of a height which is less than their height in the region of reduced height.

17. (CURRENTLY AMENDED) The oil pan of claim 16 ~~[[1]]~~, wherein there are three channels.

18. (ORIGINAL) The oil pan of claim 7, wherein the cover plate has an upright portion, the upright portion having a securing flange at an end thereof remote from the horizontal portion.

19. (ORIGINAL) The oil pan of claim 18, wherein the upright portion is substantially coplanar with the end surface.

20. (ORIGINAL) The oil pan of claim 18, wherein a plurality of bolt holes are provided in each of the securing flange and the horizontal portion.

Application No. 10/027,814  
Amendment dated January 25, 2005  
Reply to Final Office Action of November 26, 2004

21. (ORIGINAL) The oil pan of claim 20, wherein bolt holes are not provided in the upright portion.